THIRD-ORDER LEVELING
NATIONAL GEODETIC VERTICAL DATUM OF 1929

37-082-14
NAUGATUCK QUADRANGLE
30 W.VA.-136 KY.
N3745-W8215/15
DIAGRAM NJ 17-7
JENKINS

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY


Lawrence and Martin Counties, Kentacky; Lincoln, Mingo, Wayne Counties, West Virginia

Final adjustment of 1973

Edition of 6/21/77

PR: WSM/sws

WAYNE (41)



INEZ (137)

WILLIAMSON (112 KY.-W.VA. 20)

NGS (USCSGS) VERTICAL CONTROL DATA

A. Quadrangle 370821

HOLDEN (29)

INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.	MARK (USGS)	PAGE NO.
594	3	58 RHP 1959 757	4
603	3	59 RHP 1959 751	5
615	3	112 RHP 1959 782	5
617 KY	4	113 RHP 1959 876	5
619	3	114 RHP 1959 748	5
621	3	115 RHP 1959 643	6
623	3	116 RHP 1959 693	6
629 KY	4	117 RHP 1959 1308	6
634	3	118 RHP 1959 786	7
638	3	119 RHP 1959 822	7
639	3	120 RHP 1959 1324	7
645	3		
649 KY	4	NGS	
672	3		
704	4	บ 148 1957	5
722	4	R 150 1957	7
746	3	v 158 1957	6
781	3	X 158 1957	6
818	3	C 161 1957	4
57 RHP 1959 77	5 4		

ISOLATED BENCH MARKS (By S. R. Archer, 1914; Book A9587)	<u>Feet</u>
Nolan, 2.3 mi NW. of; 130 ft NW. of rd. crossing; 100 ft W. of mile- post 480; 70 ft N. of deserted house; in 15- by 108- by 10-ft. sandstone boulder; standard tablet stamped "645" (Reported not	
found, 1953)	644.657
Naugatuck; at E. end of siding; 25 ft S. of RR.; 100 ft W. of old rd. crossing; in sandstone culvert; standard tablet stamped "638" (Not found, 1963)	637.427
Naugatuck, 1.9 mi NW. of; 200 ft N. of RR. crossing; 75 ft W. of wagon rd.; in sandstone rock; standard tablet stamped "639" (Reported not found, 1953)	638.368
Kermit; 600 ft E. of station; on W. side of sandstone culvert; in third tier of stone below top; standard tablet stamped "623" (Reported not found, 1953)	622.500
Kermit; 2.5 mi NW. of; 100 ft N. of RR.; 300 ft NE. of RR. crossing; 50 ft N. of wagon rd.; 5 ft S. of gate; in sandstone rock; standard tablet stamped "621" (Reported no found, 1953)	620.365
Crum, 0.3 mi E. of; 50 ft N. of RR.; on S. side of county rd.; 100 ft NW. of milepost "Naug. 11"; in sandstone boulder; standard tablet stamped "619" (Not found, 1953)	618.742
Jennie; 10 ft S. of NW. entrance to RR. tunnel; 150 ft E. of rd. crossing; in concrete post; standard tablet stamped "615" (Reported no found, 1953)	614.366
Millet, 1.6 mi NW. of; in E. end of N. abutment of RR. bridge 756 over Camp Creek; standard tablet stamped "603" (Reported not found, 1953)	602.040
Blocton, 2.4 mi E. of; 0.22 mi W. of Eugene Post Office; 35 ft S. of rd. crossing; in sandstone rock; standard tablet stamped "634"	633.780
Lenore, 3.0 mi N. of; in E. bridge seat of N. abutment of RR. bridge 941; standard tablet stamped "672"	671.946
Breeden, 800 ft E. of; in top of S. end of E. abutment of RR. bridge 956; standard tablet stamped "818" (Not found, 1960)	818.278
Wilsondale, 1.8 mi SE. of; 8 ft N. of RR.; 740 ft W. of Mingo- Wayne County line; in sandstone ledge; standard tablet stamped "781" (Not found, 1960)	780.879
Doane, 3.0 mi SE. of; in top of W. bridge seat of S. abutment of RR. bridge 967 over Gourd Branch; standard tablet stamped "746" (Not found, 1960)	745.801
Webb, 1.8 mi NW. of; 105 ft N. of milepost "Naug. 20," on N. side of wagon rd.; on E. side of Coon Hollow; in sandstone rock; standard tablet stamped "594" (Reported destroyed, 1953)	593.925

			•	
]	SOLAT	ED BENCH	MARKS (Cont'd.)	Feet
I	oane, tabl	0.4 mi et stamp	E. of; 10 ft N. of RR. track; in sandstone rock; standard	
P	resto	n, 0.6 m	i E. of; 800 ft E. of Wells Branch station; in NW. bridge 975 over mouth of Missouri Branch; standard ed "704"	722.275
	Cabi	er sramb	ea "704"	704.565
r	Zu C	ob or M.	ffice, 400 ft S. of; 250 ft E. of mouth of Emely Creek; end of S. stone abutment of wooden hwy. bridge over standard tablet stamped "617 KY"	617 2/2
P			i SW. of post office, along graveled rd.; at mouth of	617.242
	conci	rete wal	Fork; 285 ft S. of junction of rd. S.; in E. end of N. l of approach of steel hwy. bridge over Wolf Creek; let stamped "629 KY"	
				629.389
M	Wolf	Creek; c	ffice, 1.36 mi SW. of; 200 ft E. of bend in Wolf Creek of mouth of Laurel Lick Branch N.; at N. bank of on S. side of rd.; in top of large sandstone rock; et stamped "649 KY" (Reported not found, 1954)	
				6 49.101
_			LINE 1.	
В	7 R. H	. Paine,	1959; Book AV 686	
6	3 8	0.00	"C 161 1957" (NGS)	788.729
6	41	1.78	Breeden, 3.7 mi N. of, thence 1.8 mi NW.; 1.1 mi SE. of Mt. Sinai School; 25 ft NE. of rd.; 75 ft NE. of East Fork Twelvepole Creek; 50 ft NW. of drain; set vertically in S. face of large embedded boulder; standard tablet stamped	
			"57 RHP 1959 775"	775.723
6	41	1.78	Reference mark; 60 ft W. of tablet; in base on N. side of 28-in. beech tree; rail spike	770.66
6	43	2.56	U.E., on S. edge of rd. at drain crossing; on rock; chiseled square	775.56
6	44	3.20	McComas, 3.2 mi S. of; 0.5 mi NW. of Mt. Sinai School; at Y-rd. fork; 16 ft N. of rd.; 6 ft E. of drain; in top of boulder; standard tablet stamped "58 RHP 1959 757"	757.48 7
6	44	3.20	Reference mark; 80 ft SW. of tablet; in base on	
			N. 8100 Of 70-in booch took	754.93

NAUGATUCK QUADR	ANGLE 30 W.VA136 KY.	37-083-14 5
LINE 1 (Cont'd.)	Feet
6 46 4.21	U.E., 240 ft E. of Y-rd. fork; on boulder; chiseled square	751.52
6 48 5.13	McComas, 1.2 mi S. of; 40 ft W. of graded rd.; 25 ft N. of N. end of cleared field; 34 ft NW. of W. end of corrugated metal culvert; set vertically in E. face of large embedded boulder; standard tablet stamped "59 RHP 1959 751"	750.854
6 48 5.13	Reference mark; 25 ft SE. of tablet; on top of small embedded boulder; chiseled square	742.27
	LINE 2.	
By R. H. Paine,	1959; Book AV 806	
6 2 0.00	"U 148 1957" (NGS)	730.461
6 5 1.45	Dunlow, 6.0 mi S. of, along U. S. Highway 52, thence 1.2 mi SE.; 42 ft W. of, and 8 ft higher than centerline of rd.; 37 ft W. of Moses Creek; at mouth of small hollow; set vertically in S. face of 11- by 20-ft boulder; standard tablet stamped "112 RHP 1959 782"	781.783
6 5 1.45	Reference mark; 32 ft E. of tablet; on W. edge of creek and rd.; on boulder; chiseled square	776.66
6 10 3.20	Dunlow, 6.0 mi S. of, along U. S. Highway 52, thence 3.0 mi SE.; 1.4 mi N., thence 1.2 mi N. of Walnut Grove School; 90 ft N. of Moses Creek; 80 ft NW. of, and 9 ft higher than centerline of rd. at trail crossing; 5 ft NE. of trail; 11 ft higher than centerline of trail at creek; 13 ft N. of 32-in. beech tree; in rock outcrop; standard tablet stamped "113 RHP 1959 876"	875,488
6 10 3.20	Reference mark; 54 ft E. of tablet; in base on NW. side of 28-in. beech tree; rail spike	876.08
6 15 4.43	Walnut Grove School, 1.4 mi N. of; 28 ft S. of, and 2 ft higher than centerline of intersection of rd. and jeep trail N.; 70 ft SE. of, and 5 ft higher than crossing of trail and Old Fork Creek; 15 ft SE. of rd.; 4 ft N. of 10-in. walnut tree; in concrete post; standard tablet stamped "114 RHP 1959 748"	747.550

LI	NE 2	(Cont'd.)	<u>Feet</u>
6	18	5.93	Walnut Grove School, 500 ft S. of; 150 ft N. of, and 4 ft higher than centerline of junction of T-rd. fork; 20 ft E. of rd.; 2 ft SE. of gas pipeline; set vertically in W. face of rock cut; standard tablet stamped "115 RHP 1959 643"	643.343
6	19	5.96	Reference mark; 140 ft SW. of tablet; in top of E. end of N. headwall of concrete culvert; head of rail spike set in cement	636.96
6	23	7.85	Walnut Grove School, 2.0 mi SE. of; 0.2 mi S. of Mingo-Wayne County line; 25 ft NE. of, and 4 ft higher than centerline of graded rd.; 28 ft NW. gas pipeline; set vertically in SW. face of large rock cut; standard tablet stamped "116 RHP 1959 693"	692.595
6	23	7.85	Reference mark; 125 ft NW. of tablet; opposite house; on ledge of rock at cut; chiseled square	689.73
6	26	9.18	U.E., 30 ft SW. of, and 0.5 ft lower than center- line of junction of T-rd. fork; on W. end of N. stone abutment of bridge; chiseled square	736.63
6	27	9.95	"V 158 1957" (NGS)	770.681
			LINE 3.	
Ву	R. H	. Paine,	1959; Book AV 806	
6	29	0.00	"X 158 1957" (NGS)	943.181
6	29	0.17	U.E., 70 ft SE. of, and 2 ft higher than center- line of junction of Y-rd. fork; on S. end of W. stone abutment of bridge; chiseled square	877.63
6	32	1.29	Selwyn, 5.4 mi NE. of, thence 1.1 mi SE.; at saddle between Jennie Creek and Messer Branch; 34 ft SW. of, and 2 ft higher than junction of jeep rd. and foot path in saddle; 7 ft N. of two 10-in sassafras trees; in concrete post; standard tablet stamped "117 RHP 1959 1308"	1308.025
6	33	1.36	Reference mark; 300 ft NE. of tablet; 3 ft SW. of foot trail, in top of embedded RR. rail	1259.03

LI	NE 3	(Cont'd.	.)	<u>Feet</u>
6	38	2.89	Selwyn, 6.5 mi E. of, along Marrowbone Creek; at mouth of Messer Branch; 120 ft E. of, and 3 ft higher than centerline of junction of Y-rd. fork; 18 ft N. of rd.; set vertically in SW. face of large embedded boulder; standard tablet stamped "118 RHP 1959 786"	
6	3 8	2.89	Reference mark; 58 ft S. of tablet; in base on N. side of 18-in. sycamore tree; rail spike	783.54
6	41	4.66	Selwny, 6.0 mi E. of; 0.7 mi E. of mouth of Big Laurel Branch; 90 ft NW. of, and 0.3 ft lower than centerline of junction of Y-rd. fork; 18 ft NE. of rd.; in top of embedded boulder; standard tablet stamped "119 RHP 1959 822"	821.612
6	41	4.66	Reference mark; 138 ft SE. of tablet; 50 ft E. of Y-rd. fork; on embedded boulder; chiseled square	825.72
6	48	6.67	Lenore, 1.9 mi NE. of, thence 2.3 mi NW.; 0.7 mi E. and 2.0 mi S. of mouth of Big Laurel Branch; 260 ft N. of, and 30 ft lower than centerline of crossroads at saddle; 320 ft S. of, and 14 ft higher than centerline of rd. crossing and small pipeline; 20 ft E. of rd.; in top of NE. corner of 18- by 25-ft boulder; standard tablet stamped "120 RHP 1959 1324"	1324.202
6	49	6.91	Reference mark; at crossroads at saddle; on ledge	1324.202
			rock in rd.; chiseled square	1372.65
6	52	7.94	U.E., 15 ft NW. of, and 0.6 ft lower than center- line of junction of Y-rd. fork; on rock; chiseled square	720.33
6	54	8.99	"R 150 1957" (NGS)	660.045

HORIZONTAL CONTROL NORTH AMERICAN DATUM OF 1927

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY


37-082-14
NAUGATUCK QUADRANGLE
30 W.VA.-136 KY.
N3745-W8215/15
DIAGRAM NJ 17-7
JENKINS

Lincoln, Mingo, and Wayne Counties, W.Va.; Lawrence and Martin Counties, Ky.

Edition of 1/25/77

PR: CRV/rmm

Plane coordinates are based on Lambert projection, West Virginia, South Zone, and Kentucky, South and North Zones Only the permanent marks are listed for control classified obsolete and are not shown on sketch



DISCLAIMER

We no longer attest to the validity of the positions listed for horizontal control established by transit traverse procedures. This control is now considered OBSOLETE and is included in this list for the purpose of identification only.

INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.
629 KY TT 35 TWC 1951 TT 36 TWC 1951 TT 36 TWC 1951 602.105 TT 38 TWC 1951 649.339 TT 41 TWC 1951 690.018 TT 42 TWC 1951 TT 43 TWC 1951 TT 45 TWC 1951 TT 60 TWC 1951 TT 60 TWC 1951 TT 61 TWC 1951 TT 63 TWC 1951 TT 64 TWC 1951 TT 65 TWC 1951 TT 66 TWC 1951 TT 67 TWC 1951	43333344444445555
USED T 8 A T 23 A 1942 T 24 A 1942	3 6 6
NGS	
L 46 1935 633.188 M 46 1935 632.486 Q 46 1935 R 46 1935 S 46 1935	5 5 5 6

STATION DESCRIPTION PLANE COORDINATES. FEET

LAT ITUDE 0 1 11 LONGITUDE 0 1 11

The following positions are considered OBSOLETE. To be used only to locate permanent marks in the field.

By T. W. Cayce, 1951-52; Book AH 270

Webb, 1.7 mi NE. of station, along Morfolk and Western Railway; 30 ft NE. of signal booster box; 16 ft E. of E. rail; 9 ft SE. of milepost NA-20; in concrete post; standard tablet stamped "TI 35 TWC 1951" (Reported destroyed, 1960)

Ky. S.) X = 2.947.215 Y = 616.762

37 58 55.32

82 27 47.44

Webb, 0.2 mi S. of station, along River Road; 252 ft NW. of milepost NA-18; 101 ft S. of telephone pole; 63 ft W. of rail; 44 ft NW. of telephone pole; in concrete post; USED standard disk stamped "T 8 A" (Not found, 1962)

X = 2.941.644 Y = 610.149

37 57 51,90

82 28 59.83

Tripp, 1.4 mi N. of station, along N. & W. Ry.; at rd. crossing between tunnels No. 6 and No. 7; 530 ft NE. of milepost NA 15; 120 ft W. of rd. crossing; 28 ft NW. of near rail of westbound track; in concrete post; standard tablet stamped "TT 36 TWC 1951"

X = 2.939.837

Y = 599.421

37 56 06.54

82 29 27,00

Inez. 0.6 mi E. of post office, along State Highway 40, thence 5.2 mi NE. along Turkey Creek Road; 150 ft NW. of Mouth of Turkey Creek School; 68 ft N. and 75 ft E. of junction of Y-rd.; 3 ft W. of NW. corner of schoolyard; in concrete post; standard tablet stamped "TT 37 TWC 1951 602.105" (Reported destroyed, 1962)

X = 2.941.336 Y = 592.074

37 54 53.42

82 29 11.48

Inez. 0.6 mi E. of post office, along State Highway 40, thence 3.6 mi NE. along Turkey Creek Road; 75 ft NW. of NW. corner of Head of Turkey Creek School; 55 ft SW. of centerline of rd. at large concrete culvert; 30 ft S. of intersection of drive to school; in concrete post; standard tablet stamped "IT 38 TWC 1951 649.339"

X = 2.938.730

Y = 583.255

37 53 27.17

82 29 47.76

Inez. 3.9 mi SE. of post office, along State Highway 40; 27 ft ME. of centerline of hwy.; 29 ft E. of junction of driveway N.; 12 ft SE. of SW. corner of school bus waiting station; in concrete post; standard tablet stamped "TT 41 TWC 1951 690.018"

X = 2.941.267 Y = 563.284

37 50 08.94

82 29 24.70

Inez. 5.0 mi SE. of post office, along State Highway 40, thence 0.7 mi SE.; at mouth of Hog Pen Hollow; 11 ft E. of centerline of rd.; 110 ft S. of SW. corner of porch at residence of John H. McCoy; 14 ft S. of E. abutment of small stone culvert; in concrete post; standard tablet stamped "TT 42 TWC 1951"

X = 2.947.526 Y = 558.488

37 49 19.46

82 28 08.84

STATION

DESCRIPTION PLANE COORDINATES, FEET LATITUDE 0 1 11

ONGITUDE 0 1 11

OBSOLETE MARKS (Cont'd.)

Inez, 5.0 mi SE. of post office, along State Highway 40, thence 2.7 mi SE.; 24 ft S. and 12 ft E. of centerline of rd. at drain E.; 11 ft SE. of centerline of rd.; 130 ft S. of SW. corner of porch of residence of Abe Priest; in concrete post; standard tablet stamped "TI 43 TWC 1951"

Ky. S.) X = 2.947.802 Y = 550.084

37 47 56.33

82 28 09.03

Pilgrim, 2.1 mi SW. of post office, along graveled rd.; at store of Lucian B. Gauze; in ME. corner of concrete porch e≸ store; standard tablet stamped "TT 44 TWC 1951"

X = 2.955.013 Y = 545.049

37 47 04-09

82 26 41.44

Pilgrim, 2.2 mi SW. of post office, along graveled rd.; at mouth of Pigeonroost Fork; 285 ft S. of junction of rd. S.; in E. end of M. concrete wall of approach of steel hwy. bridge over Wolf Creek; standard tablet stamped "629 KY"

X = 2.955.168

Y = 544.831

37 47 01.89

82 26 39.60

Pilgrim, 2.1 mi SW. of post office, along graveled rd., thence 1.3 mi S. along graveled rd., thence 0.5 mi SW. along Petercove Road; 21 ft N. of centerline of rd.; 77 ft NW. of NW. corner of log barn; 45 ft S. of center of creek; in concrete post; standard tablet stamped "TT 45 TWC 1951"

X = 2.952.805 Y = 537.580

37 45 51.06

82 27 12-17

Tripp, 0.2 mi SE. of station, along N. & W. Ry.; at SE. end of tunnel No. 5 of eastbound track: 3 ft SW. of near rail; in SW. end of concrete retaining wall for tracks; standard tablet stamped "TT 60 TWC 1951"

X = 2.943.391 Y = 596.007

37 55 31.57

82 28 44-14

Crum, 1.0 mi NW. of station, along N. & W. Ry.; at sharp curve in hwy.; 31 ft SW. of centerline of eastbound track: 7 ft N. of telephone pole; in concrete post; standard tablet stamped "TT 61 TWC 1951" (Not found, 1962)

X = 2.950.107 Y = 590.457

37 54 34.43

82 27 22.80

Crum. 1.2 mi SE. of station, along N. & W. Ry.; 127 ft W. of milepost NA 10; in NW. corner of concrete base of semaphore No. 42-L; standard tablet stamped "TI 62 TWC 1951"

X = 2.957.935

Y = 583.571

37 53 23.69

82 25 48.20

Kermit, 2.9 mi NW. of station, along N. & W. Ry.; 48 ft E. of semaphore No. 34-R; 12 ft N. of N. rail of westbound track; 2 ft N. of milepost NA 8; in concrete post; standard tablet stamped "TT 63 TWC 1951"

X = 2.963.714 Y = 576.426

37 52 11.08

82 24 39.31

STATION DESCRIPTION PLANE COORDINATES, FEET

LAT ITUDE 0 1 11 LONGITUDE 0 1 11

OBSOLETE MARKS (Cont'd.)

Kermit, 1.6 mi NW. of station, along N. & W. Ry.; 150 ft S. of S. entrance to tunnel No. 3; in S. headwall of open culvert along W. side of tracks; standard tablet stamped "TT 64 TWC 1951" (Reported destroyed, 1960)

Ky. S.) X = 2.963.032 Y = 571.589

37 51 23,53

82 24 49-94

Kermit; 200 ft S. of SE. corner of N. & W. Ry. station; 38 ft E. of E. rail; set vertically in W. face of stone retaining wall at rear of Muncy Cash Store; NGS standard disk stamped "L 46 1935 633.188"

X = 2.965.084

Y = 564.894

37 50 16.66

82 24 27.32

Lovely, 1.0 mi SW. of post office, along State Highway 40; at Buck Branch Coal Company; 20 ft S. and 32 ft E. of centerline of rd. across river at junction of Highway 40; 23 ft S. of school bus station; in concrete post; standard tablet stamped "TT 65 TWC 1951"

X = 2.963.232

Y = 558,401

37 49 13-16

82 24 53.25

Lovely, 3.6 mi SW. of post office, along State Highway 40; at Mouth of Emily School; in SW. corner of schoolyard; 105 ft S. of front entrance to school; 80 ft N. of junction of Y-rd.; 21 ft NE. of centerline of rd.; in concrete post; standard tablet stamped "TT 66 TWC 1951 629.001"

X = 2.961.809 Y = 550.416

37 47 54.76

82 25 14.49

Kermit, 1.9 mi SE. of station, along N. & W. Ry.; 0.3 mi NW. of milepost NA 3; at SE. end of tunnel No. 1; 6 ft SW. of SW. rail; set vertically in SE. face of portal; NGS standard disk stamped *M 46 1935 632.486*

X = 2.971.007 Y = 558.218

37 49 08.63

82 23 16.50

Naugatuck, 2.0 mi NW. of station, along N. & W. Ry.; 83 ft N. of Ry. signal box; 16 ft E. of near rail of westbound track; 2 ft E. of milepost NA 2; in concrete post; standard tablet stamped "TT 67 TWC 1951"

X = 2.974.629 Y = 552.724

37 48 13.07

82 22 33.84

Maugatuck, 0.3 mi NW. of station, along N. & W. Ry.; at junction of spur track E. to Lenore; at water tank; in S. corner of concrete base of S. pedestal; NGS standard disk stamped "Q 46 1935"

X = 2.982.625

Y = 548.721

37 47 30,69

82 20 56.07

Naugatuck, 0.2 mi W. of station, along N. & W. Ry.; at SE. end of bridge 934 over Pigeon Creek; at top of slope of wing; in SE. backwall; MGS standard disk stamped "R 46 1935"

X = 2.982.516

Y = 548.047

37 47 24.07

82 20 57.73

STATION DESCRIPTION
PLANE COORDINATES, FEET

LATITUDE . .

LONGITUDE

OBSOLETE MARKS (Cont'd.)

Naugatuck, 2.0 mi SE. of station, along N. & W. Ry.; O.2 mi NW. of milepost N. 482; 34 ft NE. of NE. rail; at residence of Joe Davis; at W. corner of yard; in concrete post; NGS standard disk stamped "S 46 1935"

Ky. S.) X = 2,990,696

Y = 542,651

37 46 27.83

82 19 18.33

Maugatuck, 3.3 mi SE. of station, along N. & W. Ry.; 246 ft SW. of milepost N. 481; 16 ft S. of centerline of U.S. Highway 52; 41 ft NW. of end of picket fence; 14 ft W. of end of guard fence; in concrete post; USED standard disk stamped "T 23 A 1942" (Not found, 1960)

X = 2,989,327

Y = 538,473

37 45 47.04

82 19 37.26

Nolan, 1.4 mi S. of station, along N. & W. Ry.; 198 ft S. of milepost N. 479; 29 ft S. of gatepost; 28 ft E. of centerline of track; 27 ft SW. of end of guardrail; in concrete post; USED standard disk stamped "T 24 A 1942" (Not found, 1960)

X = 2,991,456

Y = 535,354

37 45 15.46

82 19 12.17

Eull. 496, p. 122

Station: ANTHONY County: Mingo W. Va. Observer: E. L. McKair Year:1909 Datum: 1927 N.A.D. by graph

Description:

On high, cleared knob between the waters of Marrow-bone and Jenny's Creeks and at the head of Neely Eranch of Marrow-bone. Land is owned by Stanley Erisden. Station may be reached either from Marrow-bone or Jenny's Creeks.

Signal: A quadripod of usual form.

Station mark: A round-headed tolt set in 23 inch by 12 inch by 12 inch sandstone.

Reference marks: No. 1 is an earthenware crock set 12 inches below surface, distant 9.76 feet, true azimuth 229°39'. No. 2 is a chisel mark on an 8-inch by 15 inch by 2 inch sandstone set 12 inches below surface, distant 9.58 feet, true azimuth 322°30'.

[Latitude	37 52	44	.78			Longit	tude 82	19 13	.63 [
To Station—	Azimuth				Back Azimuth				Distance	
	•	,			•			Log. N	eters	Miles
Flag Hurricane Nelson Runyon Chestnutcamp	31 55 103 276 339	43 59 08 22 34	53 18 58 68 42		211 235 252 96 159	37 52 53 26 37	35 56 35 25 27	4.450 4.261 4.570 3.091 4.247	+726	
	!	2		8					12. v	
	MTTED OT				٠,		***			

otation: HURRICANE(USGS)(USC&GS)

County:

Martin

State: Ky

Description:

2/19/54 mcs

Observer: Ky. By Products Coal Year: 1929 Datum:

1927 N.A.D.

Company

PUBLICATION COPY In Martin County - On a high cleared knob on ridge between Wolf Creek and Rockcastle Creek. At head of Big Crooked Branch of Wolf Creek, Walnut Fork of Coldwater Fork of Rockcastle Creek and Hurricane Fork of Jack Cassady Branch of Coldwater.

Station Mark - U.S.G.S. aluminum triangulation (25-ft. wood tower exactly centered over station was built by C.C.C. during winter of 1935) tablet cemented 16- by 24-in. boulder set flush with

Reference mark No. 1 - Cross mark of rock ledge at W. end of knob 148.94 ft. from station in true azimuth 38°4

Reference mark No. 2 - Nail in root of 18 in hickory tree, 21.43 ft. from station in true azimuth 220°36'

Reference mark No. 3 - Nail 4 ft. above ground in 7-in. pine tree on side of knob, 34.11 ft. from station in true azimuth 336°25'

X = 2,940,922

Y = 545,211

[Latitude3	7 47 10.527	Longitude82 2	9 36.780	1
To Station—	Azimuth	Back Azimuth	Feet Dist	ance
Maynard Walnut Panther Hickory Goble Mudlick Jones Standifer (USGS) Spring Knob Handmaul Saltwell Preston Brown Turkey Flatrock Blankenship Buck Flag (USGS)	06 12.8 06 12.8 06 12.8 06 12.8 06 12.8 07 02.2 18.5 19.5	96 04 52.8 226 37 05.6 232 37 41.6 244 59 04.2 250 45 01.2 260 33 52.1 274 26 19.6 276 23 53.2 283 36 12.8 303 00 52.1 312 28 34.8 323 32 15.4 335 12 30.8 350 27 17.0 353 42 27.3 355 46 44.9 37 03 12.8 179 30 15.0	34599.30 12127.8 41760.21 28794.8 35728.27 22755.9 17793.35 56191.92 47047.38 51274.00 28274.15 34253.8 41223.1 40463.56 3076.1 61658.56 29294.5 46625.05	Miles

Observer: Ky. By Products Coal Year: 1929 Datum: Prelim. 1927 NAD

PRELIMINARY

1: 2/18/54 mcs

PUBLICATION COPY

In Martin County - On a knob on ridge between Buck Creek and Tug River. This station is WNW. about 1 mile from mouth of Buck Creek. It may be reached by going up first right hand hollow off Buck Creek to its head and following ridge to left about 3/8 mile.

Station Mark - Houston Triangulation Survey tablet cemented in a 7- by 9- by 27-in. stone set on end and projecting 2 in. above ground.

Reference mark No. 1 - Nail 5.5 ft. above ground in 18-in. hickory tree 108.40 ft. from station in true azimuth 233°27'

Reference mark No. 2 - Nail in 12-in. locust stump, 11.35 ft. from station in true azimuth 293°20'

Reference mark No. 3 - Nail in root of 24-in. white-oak (corner tree), 30.42 ft. from station in true azimuth 343°48'

X = 2,957,742

Y = 569,195

Destroyed 1954.

Latitude 37 51 01.717

Longitude 82 25 56.900

[Latitude 3	3/ 51 01./1/	Longitude 82 25 56.900]				
To Station—	Azimuth	Back Azimuth	Distance			
· Hurricane (USGS) ·Blankenship	37 03 12.8 149 51 00.8	217 00 57.9 329 48 11.0	Feet Miles 29294.5 44079.1			
			37-45			
Form 9-1678		•				

Form 9-1078

S. SOVERABERT PRESTING SPYICE 16-55573-